

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Aerosol 2K Polyurethansystem Klarlack glaenzend
- **(Article number) product ID.:** REZ1185
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU21 Consumer uses: Private households / general public / consumers
- **Application of the substance / the mixture:** painting
- **Uses advised against** No further relevant information available.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - Peter Kwasny GmbH
 - Heilbronner Str. 96
 - D-74831 Gundelsheim
- Tel.: 0049-(0)6269-95-20
E-mail: labor@kwasny.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Tel.: +49 6269 95 20 (MO-FR 7.15-15.15)
- **national:**
 - National Poisons Information Service, Birmingham
 - Tel.: 844 892 0111
- **K-Nr.** 0001

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
- The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** *Danger*· **Hazard-determining components of labelling:***Aliphatic polyisocyanate (HDI oligomers, isocyanurate)**acetone**n-butyl acetate**Solvent naphtha (petroleum), light arom. benzene < 0,1 %**Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate**2,3-epoxypropyl neodecanoate*· **Hazard statements***H222 Extremely flammable aerosol.**H229 Pressurised container: May burst if heated.**H319 Causes serious eye irritation.**H317 May cause an allergic skin reaction.**H336 May cause drowsiness or dizziness.**H412 Harmful to aquatic life with long lasting effects.*· **Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P103 Read carefully and follow all instructions.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P211 Do not spray on an open flame or other ignition source.**P251 Do not pierce or burn, even after use.**P271 Use only outdoors or in a well-ventilated area.**P273 Avoid release to the environment.**P302+P352 IF ON SKIN: Wash with plenty of water.**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P312 Call a POISON CENTER/doctor if you feel unwell.**P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**P337+P313 If eye irritation persists: Get medical advice/attention.**P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Additional information:***EUH018 In use, may form flammable/explosive vapour-air mixture**EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.**6.5 % of the mixture consists of component(s) of unknown toxicity.**EUH204 Contains isocyanates. May produce an allergic reaction.*· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-<25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	10-<25%
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17-xxxx	Aliphatic polyisocyanate (HDI oligomers, isocyanurate) Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. benzene < 0,1 % Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335; STOT SE 3, H336	2.5-<5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47-xxxx	2-butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-<2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<1%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40-xxxx	Bis(1,2,2,6,6-penthamethyl-4-piperidyl)sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.1-<0.25%
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33-xxxx	2,3-epoxypropyl neodecanoate Muta. 2, H341; Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.1-<0.25%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media -**
- **Suitable extinguishing agents:** Cool container with water
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm
Long-term value: 133 mg/m³, 20 ppm
Sk

1330-20-7 xylene, mixture of isomers

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

· Regulatory information WEL: EH40/2020

· Ingredients with biological limit values:

1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

· Regulatory information BMGV: EH40/2011

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

(Contd. on page 6)

GB

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 5)

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Aerosol

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

-24.9 °C

· Flammability

Not applicable.

· Lower and upper explosion limit

· Lower:

1.2 Vol % (123-86-4 n-butyl acetate)

· Upper:

18.6 Vol % (115-10-6 dimethyl ether)

· Flash point:

-42 °C (115-10-6 dimethyl ether)

· Auto-ignition temperature:

235 °C (115-10-6 dimethyl ether)

· Decomposition temperature:

Not determined.

· pH

Mixture is non-polar/aprotic.

· Viscosity:

· Kinematic viscosity

Not determined.

· Dynamic:

Not determined.

· Solubility

· water:

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value)

Not determined.

· Vapour pressure at 20 °C:

3,400 hPa (115-10-6 dimethyl ether)

· Density and/or relative density

· Relative density

0.8125 g/ml

· Vapour density

Not determined.

(Contd. on page 7)

GB

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 6)

· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
· Solvent content:	
· Organic solvents:	80.7 % With propellant gas. Content given by weight.
· VOC (EU)	(<840g/l) 80.66 %
· Solids content:	16.3 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 7)

· **LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Dermal	LD50	69,480 mg/kg
Inhalative	LC50/4 h	21.8 mg/l

115-10-6 dimethyl ether

Inhalative	LC50/4 h	308 mg/l (rat)
------------	----------	----------------

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

28182-81-2 Aliphatic polyisocyanate (HDI oligomers, isocyanurate)

Inhalative	LC50/4 h	1.5 mg/l (ATE)
------------	----------	----------------

64742-95-6 Solvent naphtha (petroleum), light arom. benzene < 0,1 %

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

112-07-2 2-butoxyethyl acetate

Oral	LD50	2,400 mg/kg (rat)
Dermal	LD50	1,580 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

1330-20-7 xylene, mixture of isomers

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat) 4h

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

26761-45-5 2,3-epoxypropyl neodecanoate

Oral	LD50	>9,600 mg/kg (rat)
Dermal	LD50	>3,800 mg/kg (rabbit)
Inhalative	LC50/4 h	>5 mg/l (rat)

· **Primary irritant effect:**

- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause drowsiness or dizziness.

· **11.2 Information on other hazards**· **Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 8)

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Endocrine disrupting properties**
- The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA | <p>UN1950</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | <p>1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR | <div style="text-align: center;">  </div> <p>· Class 2 5F Gases.
· Label 2.1</p> <hr style="border-top: 1px dashed black;"/> <p>· IMDG, IATA</p> <div style="text-align: center;">  </div> <p>· Class 2.1 Gases.</p> |

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 9)

· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void not classified
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Code	Warning: Gases. - not classified F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

*

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC 2004/42/EG: <840g/l

· **Poisons Act**· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

(Contd. on page 11)

GB

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 10)

· Reportable explosives precursors

67-64-1 acetone

Listed

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU
· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:
· Technical instructions (air):

Class	Share in %
NK	50-100

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet may only be passed on to third parties for the manufacturer's brands.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing SDS: Product safety department

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

Safety data sheet according to UK REACH

Printing date 05.09.2025

Version number 1

Revision: 05.09.2025

Trade name: Aerosol 2K Polyurethansystem Klarlack glaenzend

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 ATE: Acute toxicity estimate values
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 : Aerosols – Category 3
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Muta. 2: Germ cell mutagenicity – Category 2
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
 · *** Data compared to the previous version altered.**

GB