

Instructions – Candy Paint in Spray Can

INSTRUCTIONS FOR USE – CANDY PAINT IN SPRAY CAN

Four-step transparent Candy effect – spray can application

Solvent-based acrylic spray paint.

Surface Preparation

The surface must be clean, rust-free, sanded, degreased, and perfectly smooth. Candy is transparent, so scratches, filler marks, or uneven sanding can remain visible through the final color. Use a primer filler if needed and sand it smooth after drying (grit P400–800).

Step 1 – Black Basecoat

Apply 2–3 even coats of black basecoat. Wait 5–10 minutes between coats. The goal is a uniform, fully covered black surface for the silver base. Let it flash off until matte and dry to the touch.

Step 2 – Silver / Pearlescent Metallic Basecoat

Shake the can for at least 2 minutes. Apply 2–3 thin, even coats from 20–30 cm with about 70% overlap. Wait 5–10 minutes between coats. After the last coat, allow about 40 minutes before applying Candy.

Step 3 – Candy Effect Coat

Shake the Candy can again and always keep it upright, with the nozzle on top. Apply 3–5 thin, even coats with about 10 minutes flash-off time between coats. Each extra Candy layer makes the shade deeper and darker, so test the ideal number of coats first.

Step 4 – Clear Topcoat

After the last Candy coat, allow about 40 minutes before clear coat. Apply a high-quality clear topcoat, preferably 2K for higher durability, gloss, and UV protection. Follow the clear coat manufacturer's instructions.



Application Tips:

- Apply at 18–25 °C in a dust-free, draught-free area, away from direct sun.
- Start each pass outside the part and spray with smooth, even movement.
- Do not spray too wet; Candy should be built up gradually in thin layers.
- For Candy Black Cherry, 3–4 Candy coats are usually enough.
- **Always test on a sample surface first!**
- **Always keep the spray can in a vertical position during application to ensure an even spray pattern and prevent dripping from the nozzle.**

Thank you for choosing PMcolours. Find more info and products at: www.pmcolours.com