Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de



SprayMax®

1K Silicon remover 400 ml

Part no. 680090

Product

Description / Purpose

Rich in active ingredients, mild cleaning agent for the eficient removal of silicone, grease, oil, wax, dirt, tar, and soot. This high quality silicone remover has excellent cleaning and degreasing properties and improves the adhesion to any paint coat. The product is used for the application of solventbased paints.

Properties

- Increases adhesion
- Maximum yield
- Uniform distribution
- Strong cleaning and degreasing effect
- High penetration depth on plastic parts
- Removes silicone, grease, oil, wax, dirt, tar and soot.
- Contains mild cleaning agents

Material base

Special resin combination

VOC Value (EU)

620 g/l

Substrate

Metal, plastics, glass, old paint and factory paintol which have been filled and primed; Coated and uncoated surfaces.

Processing

Protection measures




Wear personal protection equipment.
(respiratory mask/gloves/goggles)
For more information, see safety data sheet.

Shake



Shake can thoroughly for at least 2 minutes from when the mixing balls are heard.

Spraying distance



15 cm - 20 cm

Spray passes



1 light spray coat. Wipe off with a clean, dry cloth after application. Do not allow cleaned area to dry well. Repeat process if required and prolong residence time.

Processing conditions



Optimum application at 18° C - 25° C and a relative humidity from 40 - 60 %.


Additional Information

Important Information



Avoid bumps, friction and impact.

Shelf Life



10 years
The usage period refers to an unused can that is stored correctly at a temperature of 15 - 25 °C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

For professional use only.

For labelling see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.